


## Air Beams - Technical Specifications

A-TYPE BEARINGS - STANDARD LIFT CAPACITY						
BEARING	CAPACITY	DIMENSIONS IN INCHES			FLOW - SCFM	
		Model Number	Pounds	Diam.	Height Air Off	Height Air On
12NSG	1000	12	2.5	2.9	2	4
12NSG-HD	2000	12	2.5	2.9	4	8
16NSG	2000	16	2.5	3.0	3	5
16NSG-HD	4000	16	2.5	2.9	5	10
18NSG	2500	18	2.5	3.1	3	6
18NSG-HD	5000	18	2.5	3.0	6	12
22NSG	4000	22	2.5	3.3	4	8
22NSG-HD	8000	22	2.5	3.1	8	16
28NSG	6000	30	3.1	4.1	5	9
28NSG-HD	12000	30	3.1	3.9	9	18
34NSG	10000	36	3.4	4.6	6	12
34NSG-HD	20000	36	3.4	4.0	12	24
40NSG	14000	42	3.4	4.8	8	15
40NSG-HD	28000	42	3.4	4.3	15	30
44NSG	18000	46	3.4	4.9	9	17
44NSG-HD	36000	46	3.4	4.4	17	34



A-type Air Bearing



B-type Air Bearing

B-TYPE BEARINGS - HIGH LIFT CAPACITY						
BEARING	CAPACITY	DIMENSIONS IN INCHES			FLOW - SCFM	
		Model Number	Pounds	Diam.	Height Air Off	Height Air On
B12N	2,000	12	1.9	2.6	8	12
B15N	3,500	15	2.0	2.9	8	14
B21N	7,000	21	2.0	3.1	14	16
B27N	12,000	27	2.1	3.4	16	18
B27HD	24,000	27	2.1	3.4	20	40
B36N	20,000	36	2.6	4.3	17	24
B36HD	40,000	36	2.6	4.3	22	45
B48N	40,000	48	2.6	5.1	18	26
B48HD	80,000	48	2.6	5.1	40	50